

# CEL-FI DUO+ +

## 4G / LTE

Smart Signal Booster™

Cel-Fi DUO+ is designed to dramatically improve voice and data indoor coverage in up to three (3) bands for 4G LTE.




### Benefits:

- **5 Min Setup: Plug & Play**
- **Best Signal by 1000x**
- **Coverage and Capacity for Up to 15,000 ft<sup>2</sup> (1,400 m<sup>2</sup>) per System (Scalable)**
- **Wireless Solution—No External Antennas or Wiring**
- **Remote Monitoring and Management via Cel-Fi WAVE Platform**



**Cel-Fi WAVE** is a smartphone app that will help you get the best performance from your Cel-Fi DUO+.

Download on the  [App Store](#) or GET IT ON  [Google play](#)

### System Features

Plug and play, simple installation—no external cables, antennas, wires, or drills needed

Clean and compact industrial design

Intuitive LED User Interface (UI)

System senses three (3) bands and relays any two

Integrated antennas

Auto-configured & Self-Contained

Unlocked: Cell phones do not need to be registered with Cel-Fi to benefit

Peaceful coexistence with adjacent Cel-Fi systems

Patented 2-unit, 3-hop system

Remote software update capability

Support for the Cel-Fi WAVE mobile & desktop applications

End-to-end cellular communication encryption without additional risk of vulnerability

Mounting brackets included with every unit

### Wireless Features

Supports LTE (FDD)

Up to 100dB of system gain in each band, simultaneously

Bluetooth Low-Energy (BT LE) communications with mobile handsets

Max EIRP for Multiple carriers: 10dBm downlink and 22dBm uplink, per band

Wirelessly (5GHz U-NII) linked Network and Coverage Units

Peaceful coexistence with adjacent Wi-Fi (24 GHz & 5 GHz), femtocell, and cellular devices

Software-based optimization of integrated antenna coverage pattern which maximizes system gain and provides improved coverage and signal quality

Automatic Gain Control (AGC) based on fast real-time echo-cancellation

Advanced digital echo-cancellation (>30dB) and channel select filtering algorithms

Cel-Fi manages the power levels between the cell tower and user devices

Extremely linear RF front end

Adaptive signal equalization

Includes Nextivity's 3rd-generation six-core ARES chipset

### Mobile Network and Network Protection Features

Up to three (3) cellular bands supported; relays two (2) simultaneously

Will work with Verizon Wireless LTE and XLTE

Cel-Fi DUO+ simultaneously supports multiple channels with bandwidths anywhere from 5 to 20 MHz per radio with a total system relay bandwidth of 35 MHz

Support for 3GPP Rel 10 features

Support for E-UTRA bands 2, 13, and 4 LTE (Other configurations are available)

Seamless integration with the Macro networks

Cel-Fi boosts service only for the Operator PLMNIDs the device is authorized and configured for

Remote Access from the cloud to the Cel-Fi device (optional)

Secure and ciphered provisioning

Software-managed system intelligence prevents uplink system gain from exceeding path loss, eliminating unnecessary rise in base station noise level

Uplink Muting Mode automatically shuts down uplink cellular transmissions when no active user equipment is detected

System Registration options available

Location Lock, which ensures the device is only being used in the location it was deployed (optional)

## System Benefits

Indoor cellular coverage!  
Anyone can install the device. No special tools or knowledge required. No external antennas needed. Simply plug-in to power.  
Attractive design can be displayed, or easily placed into the background  
No setup or ongoing maintenance needed, nor reliance upon internet, GPS, or handsets to be registered with the system  
No additional equipment or professional installation required for full performance  
The three-hop two unit wireless system eliminates the requirements and installation restrictions associated with cabled connections  
Users can be assured communications are secure, through the encrypted wireless link  
The included mounts allow for the system to be wall-mounted for maximum spatial flexibility  
Registration, Software Updates, and Engineering application support, with the Cel-Fi WAVE mobile app  
Any subscriber device on boosted network will benefit from improved coverage  
Multiple systems can be deployed without concern for mutual interference  
User Interface (UI) display allows quick and easy set-up by end-user. Provides instant visual feedback, with each unit displaying system information.  
Architecture allows user to place the Coverage Unit where it's needed and the Network Unit where it gets the best donor signal  
Simplified remote maintenance of devices in the field, with Cel-Fi WAVE cloud access

## Wireless Benefits

Clear and reliable voice connections within coverage area—up to 15,000 ft<sup>2</sup> (1,400 m<sup>2</sup>)  
Bluetooth enables the system to communicate with smart phones and the Cel-Fi WAVE mobile app, improving the user experience and adding capability to the product  
Cel-Fi remains fully functional, even when there are other RF emitters present  
Ensures maximum gain—best coverage—at all times in ever changing RF environments, without user intervention  
Subscriber devices enjoy improvements in battery life  
Linearity virtually eliminates all IMD desense issues  
The highest performance, fully-certified, signal booster possible in its power class  
Maximizes signal-to-noise (SNR) ratio—provides better data rates without negatively impacting macro cells  
Allows for 30dB—which means more coverage, safely  
Real-time adapting capability ensures the best possible user experience, in actual user environments, which are constantly changing, and have a variety of Wi-Fi types and cellular signals present

## Mobile Network Benefits

Supports most network configurations of LTE for maximum interoperability  
Seamless call handoff between Cel-Fi systems or the macro  
Easily supports multiple band and frequency configurations on a cellular network with one device  
Reduce returns, customer care calls, and provide the best product experience to users  
Unlike wideband amplifiers, ensure the equipment capex benefits only your network—third-party macro cells are completely unaffected by Cel-Fi DUO+  
Network operators can be assured Cel-Fi devices are being used as intended, with registration and location lock options  
Completely network safe, doesn't degrade macro capacity  
Registration options allow control over device deployment and may be used to prevent unintended use  
Ultimate control of the installed devices resides with the network operator

## Variants

Model Number	Bands Supported
D32-2/13/66	2, 4, 13

## Radio Performance

*(check product version for specific band support)*

D32-2/13/66	Band 2	Band 13	Band 4
Frequency DL	1930-1990 MHz	746-756 MHz	2110-2155 MHz
Frequency UL	1850-1910 MHz	777-787 MHz	1710-1755 MHz
Duplex Distance	80 MHz	-31 MHz	400 MHz
Maximum Relay BW	20 MHz	10 MHz	20 MHz
	35 MHz Combined		
UL TX Power Max EIRP	22dBm	20dBm	22dBm
DL TX Power Max EIRP	10dBm per 5 MHz	10dBm per 5 MHz	10dBm per 5 MHz

## Environmental

Operating temperature: 0° to 40°C  
Storage temperature: -25° to 60°C  
Relative humidity: 5% to 95%, noncondensing  
RoHS II 2011/65/EU  
WEEE (2002/96/EC)  
ErP 2009/125/EC

## Power

12 VDC via external supply (two included)  
External supply: 100 to 240 VAC, 47 – 63Hz  
Power consumption less than 15W per unit

## Physical Specifications

Network Unit	Coverage Unit
158.5x146x59mm	158.5x146x59mm
560g	390g

## Compliance

(check individual product version for specific regional compliance)

FCC Parts: 15, 20, 22, 24, 27

EN 301 489 -1, 17, 23

EN 301 893

EN 301 908-1, 11, 15

EN 300-328

EN 62311

UL 62368-1

CSA C22.2#62368-1

IEC/EN 62368-1

3GPP TS 25.143 Rel.10

3GPP TS 36.143 Rel.10

EN 50566/62209-2/62479 (SAR)

Bluetooth SIG

Note: Certifications are regional; not all products need or have the same certifications. Please check the specific model number to determine exactly which certifications it has.

## Patents & Design

This product is covered by Nextivity, Inc., patents and patents pending. Designed by Nextivity, Inc., in San Diego, California, USA. Please refer to [cel-fi.com](http://cel-fi.com) for details.

Specifications subject to change without notice.