

GENERAL SPECIFICATIONS

| MODEL | RFR025 | RFR05 | RFR07 | RFR10-C | RFR10-A | RFR10-GN |
|--------------------------|---------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Weight (approx) | 1628 lbS | 2530 lbs | 2860 lbs | 3500 lbs | 3500 lbs | 3800 lbs |
| GVWR | 7700 lbs | 13 385 lbs | 16 500 lbs | 20 000 lbs | 23 520 lbs | 23 520 lbs |
| Loading Surface | 64" x 10'8" | 84" x 15'4" | 84" x 15'4" | 84" x 15'4" | 84" x 15'4" | 84" x 15'4" |
| Overall Length | 17.0' | 22.0' | 22.0' | 22.0' | 22.0' | 26.0' |
| Overall Width | 72" | 89" | 89" | 89" | 89" | 89" |
| Suspension | spring | spring | spring | spring | spring | spring |
| Electric Brakes | 10" | 12" | 12" | 12" | 12" | 12" |
| Tires | H78/15ST 8 plies | 235/85R16 10 plies | 235/85R16 14 plies | 235/85R16 14 plies | 235/85R16 14 plies | 235/85R16 14 plies |
| Trailer Posts | 8 x 48" | 8 x 48" | 8 x 48" | 8 x 48" | 8 x 48" | 8 x 48" |
| Tie Downs | 2 | 4 | 4 | 4 | 4 | 4 |
| Coupler Height | 18" | 21" | 21" | 21" | 21" | 21" |
| Track Width (center-to-c | 50" | 71" | 71" | 71" | 71" | 71" |
| Hub qty/bolts | 5 | 8 | 8 | 8 | 8 | 8 |
| Coupler | 2-5/16" | 2-5/16" | 2-5/16" | 2-5/16" | pintle hook | 2-5/16" |
| Pintle Hook | OPT | OPT | OPT | - | STD | - |
| | | | | | | |
| SPARE TIRE | H78/15ST 8 Plies | 235/85R16 10 Plies | 235/85R16 14 Plies | 235/85R16 14 Plies | 235/85R16 14 Plies | 235/85R16 14 Plies |
| Gooseneck-1 | OPT | X | X | X | OPT | OPT |
| Gooseneck-2 | | | | X | | |