



Double Frame Trailers

Model	Code	900R	900RA	FOR 1005	FOR 1205	FOR 1207	FOR 1610
Weight		535 lbs / 242 kg	635 lbs / 288 kg	980 lbs / 444 kg	1400 lbs / 635 kg	1430 lbs / 648 kg	1950 lbs / 884 kg
Capacity		3500 lbs / 1587 kg	4000 lbs / 1814 kg	3 Tons / 3000 kg	5 Tons / 5000 kg	7 Tons / 7000 kg	12 Tons / 12,000 kg
Recommended For		VTT	Tract 20HP	Tract 30 HP	Tract 50 HP	Tract 75 HP	Tract 100 HP
Overall Length	F	161 in / 409 cm	161 in / 409 cm	173 in / 439.42 cm	200 in / 508 cm	200 in / 508 cm	200 in / 508 cm
Overall Width	A	54 in / 137 cm	65 in / 165 cm	62 in / 157.4 cm	73 in / 185.4 cm	80 in / 203 cm	80 in / 203 cm
Coupler Height	D	13 in / 33 cm	13 in / 33 cm	15 in / 38 cm	15 in / 38 cm	15 in / 38 cm	15 in / 38 cm
Posts Height	B	25 in / 63.5 cm	25 in / 63.5 cm	41 in / 104 cm	41 in / 104 cm	41 in / 104 cm	41 in / 104 cm
Loading Length	E	93 in / 236 cm	93 in / 236 cm	112 in / 284.5 cm	128 in / 325 cm	128 in / 325 cm	176 in / 447 cm
Loading Width	C	38 in / 96.5 cm	41 in / 104 cm	55 in / 139.4 cm	60 in / 152.4 cm	66 in / 167.6 cm	66 in / 167.6 cm
Base Width	G	23.5 in / 59.7 cm	27 in / 68.6 cm	30 in / 76.2 cm	34 in / 86.4 cm	40 in / 101.6 cm	40 in / 101.6 cm



Double Frame Trailers Cont'd

Model	Code	900R	900RA	FOR 1005	FOR 1205	FOR 1207	FOR 1610
Track Center	H	44 in / 111.8 cm	53.5 in / 135.9 cm	54 in / 137.2 cm	62.75 in / 159.4 cm	69.5 in / 176.5 cm	69.5 in / 176.5 cm
Axel Rocket		1.5 in / 3.8 cm	1.75 in / 4.44 cm	2 in / 5 cm	2 in / 5 cm	2 in / 5 cm	2 in / 5 cm
Hub Holes		5 Trous	5 Trous	6 Trous	6 Trous	6 Trous	8 Trous
AG Tire		25 x 12 x 10	9.5L14	11L15/8 pl	11L15/8 pl	12.5L15 10pl	14L16.1 12 pl
Support		Cric	Cric	STD	STD	STD	STD
Tandem		Adjustable	Adjustable	Fix	Fix	Fix	Fix
Ground Clearance	K	14 in / 35.6 cm	14 in / 35.6 cm	14 in / 35.6 cm	17 in / 43.2 cm	17 in / 43.2 cm	17 in / 43.2 cm
Options							
Electric Brake		OPT	OPT	OPT	OPT	OPT	OPT
Wheel Deflector		N/A	N/A	OPT	OPT	OPT	OPT



Pole Trailers

Model	Code	FOR 2005	FOR 2205	FOR 2207	FOR 2209	FOR 2610
Weight		995 lbs / 451 kg	11856 lbs / 537 kg	1565 lbs / 710 kg	1645 lbs / 746 kg	1907 lbs / 865 kg
Capacity		3 Tons / 3000 kg	5 Tons / 5000 kg	7 Tons / 7000 kg	9 Tons / 9000 kg	12 Tons / 12,000 kg
Recommended For		Tract 30HP	Tract 40 HP	Tract 50 HP	Tract 75 HP	Tract 100 HP
Overall Length	F	190 in / 4.83 m	190 in / 4.83 m	211 in / 5.36 m	211 in / 5.36 m	240 in / 6.1 m
Overall Width	A	67.5 in / 1.75 m	67.5 in / 1.75 m	68.5 in / 2.15 m	68.5 in / 2.15 m	69 in / 2.13 m
Coupler Height	D	12 in / 30.5 cm	12 in / 30.5 cm	14 in / 35.6 cm	14 in / 35.6 cm	15 in / 38.1 cm
Posts Height	B	41 in / 104 cm	41 in / 104 cm	42 in / 106.7 cm	42 in / 106.7 cm	42 in / 106.7 cm
Loading Length	E	120 in / 304.8 cm	120 in / 304.8 cm	141 in / 358 cm	141 in / 358 cm	106 in / 431.8 cm
Loading Width	C	60 in / 152.4 cm	60 in / 152.4 cm	73 in / 185.4 cm	73 in / 185.4 cm	73 in / 185.4 cm
Base Width	G	30 in / 76.2 cm	30 in / 76.2 cm	44 in / 111.8 cm	44 in / 111.8 cm	44 in / 111.8 cm



Pole Trailers Cont'd

Model	Code	FOR 2005	FOR 12205	FOR 2207	FOR 2209	FOR 2610
Track Center	H	56.5 in / 143.5 cm	56.5 in / 143.5 cm	68.5 in / 174 cm	68.5 in / 174 cm	69. in / 173.5 cm
Axel Rocket		2 in / 51 mm	2 in / 51 mm	2 in / 51 mm	2 in / 51 mm	2 in / 51 mm
Hub Holes		6 Trous	6 Trous	6 Trous	6 Trous	8 Trous
AG Tire		11L15 / 8pl	11L15/8 pl	12.5L15 10pl	12.5L15 10pl	14L16.1 12 pl
Support		Adjustable Position				
Tandem		3 Adjustable Positions				
Ground Clearance	K	21 in / 53.3 cm	21 in / 53.3 cm	23 in / 58.4 cm	23 in / 58.4 cm	24 in / 61 cm
Overall Height	L	64 in / 1.63 m	64 in / 1.63 m	71 in / 1.80 m	71 in / 1.80 m	73 in / 1.85 m
Grid Width	M	57 in / 1.45 m	57 in / 1.45 m	72 in / 1.83 m	72 in / 1.83 m	72 in / 1.83 m
Grid Clearance	N	70 in / 1.78 m	70 in / 1.78 m	70 in / 1.78 m	70 in / 1.78 m	70 in / 1.78 m



Pole Trailers Cont'd

Model	Code	FOR 2005	FOR 12205	FOR 2207	FOR 2209	FOR 2610
Support Clearance	O	31 in / 78.7 cm	31 in / 78.7 cm	31 in / 78.7 cm	31 in / 78.7 cm	31 in / 78.7 cm
Length to Rockers	I	147.5 in / 3.75 m	147.5 in / 3.75 m	148 in / 3.76 m	148 in / 3.76 m	160 in / 4.06 m
Grid Height	J	43 in / 1.09 m	43 in / 1.09 m	49 in / 1.24 m	49 in / 1.24 m	49 in / 1.24 m
Options						
Electric or Hydraulic Brake	K	12 in / 30.5 cm	12 in / 30.5 cm	12 in / 30.5 cm	12 in / 30.5 cm	12 in / 30.5 cm

MACHINERIE
AM INC.
MACHINERY

