

FIREWOOD PROCESSOR RCA 330 JOY




- RCA 330 JOY - with a PTO Shaft
(Required Tractor Power 35 HP;
transport - 70 HP)
- Basic version with new TT 330
Discharge Conveyor
- Optional - with Oil Cooler



Suitable for logs with
diameter of 2" - 13".



The Foldable Infeed
Conveyor (6,5') of highly
resistant material.




Before the Hydraulic
Log Holder there is a
Guide Lean that guides
the log and prevents it
from hitting the log
holder. The Hydraulic
Log Holder is used to fix
the log and prevent it
from spinning and
turning.




»Joystick« - ergonomic,
safe and user friendly
operation of main
machine functions
(infeed in/out, sawing,
splitting, lifting/lowering
of the wedge...).



High cutting speed
Chain Saw 82'/s
(12,000 rpm). Cutting
with the chain saw is
quick and safe.



Hydraulic movable
limiter is adjustable
(7.8" -15.7"). Limiter
comes closer for about
1.6" every time the log
is forwarding. It returns
to its starting position
when log forwarding



The Swinging Lap remains in the horizontal position during cutting. It helps the last cut piece to fall into the splitting chute in the correct way.



Splitting Cylinder with 11 tons splitting force and quick return.

stops. Therefore the cut piece falls safely into



Lattice for Sawdust is located between the splitting wedge and the discharge conveyor.



Hydraulic Output for RCA accessories (Log Loader DM 1511 M, DM 2000 or Live Deck RN 3000 S / RN 3000 M).



Main Cover - safety switch ensures maximum safety by disengaging all major functions when cover is open.



Transport position: In-feed and Discharge Conveyor, as well as the Log Loader can be set against the machine and attached. The machine is mounted to the tractor using three point system.

Discharge Conveyor with One Stage Telescope, 10' long.



Mechanical Belt Straining



The conveyor stretches into working position with hydraulic, two-stage telescope and automatic belt tensioning.
Length - 13'.



RCA 330 JOY with TT 340 conveyor has an extra button to regulate belt speed.



Separator SP 3 for discharge conveyor TT 330 and TT 340

Separator is a accessory for Tajfun firewood processors. It can be mounted at the end of the discharge conveyor to separate the sawdust and small wood particles before the firewood falls into a bag, trailer or some other set destination.

