



Pitbull 2300 B-D

Portable Screener Quick Spec Sheet

- Isuzu 3CJI-SDZP1 water cooled 3-cylinder diesel industrial power plant rated at 20.3 HP
- 10 gallon fuel tank
- Dry element air cleaner with replaceable cartridge
- Electric start, with control panel featuring throttle control, oil pressure & overheat shutdown protection
- Machine controls and engine control panel conveniently located together for easy operator access
- Engine, oil tank, fuel tank, and control compartment fully enclosed and lockable
- Curb weight in standard pintle hook configuration 7,400 Lbs.
- Tongue weight of 2,850 Lbs.
- 6,000Lb. Dexter straight axle with electric brakes and safety breakaway controller
- Screen plant hydraulically adjusts from transport to operating position
- Positive mechanical axle locks for transport position
- 15" steel wheel 6 stud mount
- ST225/75R15 radial tires. Load range E, 8-ply rating
- Standard pintle hitch
- Standard hydraulic axle lift and park jack
- Hydraulic system over heat shut down protection
- 15 gallon hydraulic reservoir with spin-on filter and oil cooler
- Single stage gear pump providing 12 GPM at rated engine speed
- 3 section hydraulic valve with system relief
- Hydraulic direct drive shaker table featuring reverse rotation standard
- Two tier shaker table with loading apron and quick change screen panel tensioning system
- Fully welded and reinforced tubular steel frame with abrasion resistant inner bucket plate
- Screen panels fully interchangeable with all 2300 family of screening plants (both tiers)
- Common screen sizes available from 1/8" to 4" openings. Special application screen panels available

Available Options:

Customer / Dealer requests welcome.

Separation chutes for both decks

Spare tire & Wheel

Consolidation hopper under shaker table suitable to feed a separate conveyor

Lake Erie Portable Screeners
9843 Martin Ave
Lake City, PA 16423
Toll Free: 888-448-2486
Fax: 814-774-7086
info@pitbullscreeners.com