



## Grapples – Hydraulic Loaders

Model	JMS 900SR	JMS 110	JMS 130	JMS 155	JMS 170	AM 190	AM 230
Boom Length	9' / 2,74m	11' / 3,35m	13' / 3,96m	15.5' / 4,72m	17' / 5,18m	19' / 5,79m	23'
Rotation Angle	270*	360*	360*	360*	360*	360*	360*
Grapple Open	31" / 78,7cm	31" / 78,7cm	36" / 91,4cm	48" / 121,9cm	48" / 121,9cm	48" / 121,9cm	56" / 142,2cm
Grapple Close	2" / 5,08cm	2" / 5,08cm	4" / 10,61cm	4" / 10,61cm	4" / 10,61cm	4" / 10,61cm	4" / 10,61cm
Grapple Rotation	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous
Max Capacity Mid-Boom	1800 lb / 816 kg	2100 lb / 953 kg	1950 lb / 885 kg	2600 lb / 1179 kg	2300 lb / 1043 kg	3000 lb / 1360 kg	3500 lb / 1587.5 kg
Max Cap at Max Reach	1800 lb / 816 kg	2100 lb / 726 kg	1400 lb / 635 kg	1900 lb / 863 kg	1500 lb / 680 kg	2100 lb / 952 kg	3000 lb / 1360 kg
Working Pressure	2800 psi	2800 psi	2800 psi	2800 psi	2800 psi	3000 psi	3000 psi



## Grapples – Hydraulic Loaders

Model	JMS 900SR	JMS 110	JMS 130	JMS 155	JMS 170	AM 190	AM 230
Stabilizers	Telescopic						
Weight	720 lb / 326 kg	950 lb / 430 kg	1100 lb / 498 kg	1850 lb / 839 kg	1950 lb / 884 kg	1985 lb / 900 kg	2300 lbs
Attelage	Bolted	Bolted	Three pts hitch	Three pts hitch	Three pts hitch	Three pts hitch	Three pts hitch