## **Product Data Sheet**

EAS PRODUCTS - Nulite Clear Coat

Part Number: EASNL12

## **Nulite** Clear Coat

**DESCRIPTION:** Restores and protects hazy plastic headlight lenses.

## **BENEFITS:**

- Durable UV protection
- Brilliant clarity
- Easy to apply

## **PROPERTIES:**

Can size: 12.5 ozCoverage: 24 cars

Dry time: To the touch in 15 minutes. Cures in 1 hour.



**PREPARATION:** Sand the headlight with 400 grit to remove oxidation. Next, wet-sand with 1200 grit, then 2000 grit. Wipe off sanding residue with a clean towel. Apply some isopropyl alcohol on the headlight lens and wipe clean with a new paper shop towel and let dry. Wipe the lens with a new microfiber towel to remove any static dust. Apply 12" masking paper around headlight.

**APPLICATION:** Apply in temperatures above 50°. Shake can well. Hold can 6 inches from lens surface when spraying. Start at the top corner of the headlight. Spray one light coat across the lens. Move down, overlapping slightly until finished. Wipe off spray tip to prevent clogs. Replace cap after use.

**DRYING:** Air dries in one hour. Do not apply on rainy or snowy days.

**REMOVAL:** Clear coat that has not yet dried can be removed with Nulite Clear Coat Remover. Soak a paper shop towel with the remover and wipe off headlight.

**AFTERCARE**: Clean headlights with soap and water only.

**STORAGE:** Store cans in a cool dry place with adequate ventilation away from heat, sparks and flames.

**TECHNICAL CONSULTATION SERVICE:** We are ready to assist you with any questions about our products or headlight restoration. Call (706) 445-1388 for answers to your questions. Hours of operation are Monday through Friday 8:00 am until 5:00 pm ET.

**HOW TO ORDER:** Orders can be placed on our website or by calling (706) 445-1388. Website orders are generally processed faster than telephone orders.

Tel: (706) 445-1388 | Email: sales@easproducts.com | Web: nulite.pro